



Turning challenge into crossing

ACROSS CTO™

RX

- High pushability
- Seamless transition
- Outstanding crossing
- Good trackability




Mid marker

4 mm tip
Seamless Tip-to-shoulder

High RBP up to 20 Atm

Low entry
profile 0.016"



Ordering Information / Technical Information

Reference	Balloon Diameter	Balloon Length	Marker	Tip Length	Entry Profile	Max. Guidewire	Usable Length	Min. Guide Catheter / ID
110100480	1.1 mm	10 mm	1	4 mm	0.016"	0.014"	138 cm	5 F / 0.056"
110150480	1.1 mm	15 mm	1	4 mm	0.016"	0.014"	138 cm	5 F / 0.056"
110200480	1.1 mm	20 mm	1	4 mm	0.016"	0.014"	138 cm	5 F / 0.056"
150100480	1.5 mm	10 mm	1	4 mm	0.016"	0.014"	138 cm	5 F / 0.056"
150150480	1.5 mm	15 mm	1	4 mm	0.016"	0.014"	138 cm	5 F / 0.056"
150200480	1.5 mm	20 mm	1	4 mm	0.016"	0.014"	138 cm	5 F / 0.056"
200100480	2.0 mm	10 mm	1	4 mm	0.016"	0.014"	138 cm	5 F / 0.056"
200150480	2.0 mm	15 mm	1	4 mm	0.016"	0.014"	138 cm	5 F / 0.056"
200200480	2.0 mm	20 mm	1	4 mm	0.016"	0.014"	138 cm	5 F / 0.056"

Control your Size

Balloon Ø	Atm 5	Atm* 7	Atm 9	Atm* 11	Atm 13	Atm 15	Atm** 17	Atm 19	Atm** 20	Atm 21
1.1 mm	1.04 mm	1.10 mm	1.13 mm	1.16 mm	1.20 mm	1.23 mm	1.28 mm	1.38 mm	n.a	n.a
1.5 mm	1.40 mm	1.43 mm	1.47 mm	1.50 mm	1.55 mm	1.60 mm	1.65 mm	1.69 mm	1.71 mm	1.73 mm
2.0 mm	1.82 mm	1.88 mm	1.94 mm	2.00 mm	2.07 mm	2.13 mm	2.18 mm	2.22 mm	2.24 mm	2.25 mm

Atm* Nominal Pressure (NP)

Atm** Rated Burst Pressure (RBP)



The balloon material is a semi-compliant polyamide, providing a 'Work Your Size'.

Turning challenge into crossing